

GENERAL PURPOSE GRAPHITED GREASE

APPLICATIONS:

A graphite based grease, recommended for use in applications that have seen service, but still have long operating life.

- Excellent for heavy duty applications, such as rams and plungers, also chains and guide ropes on lifts and hoists
- Long lasting – service intervals extended
- Good local stress load distribution
- Fully water resistant

Colour – Black, Base – Lithium soap

PRODUCT CODE	PACKAGE SIZE	PACK SIZE	PRICE PER CARTRIDGE
General Purpose Graphited Grease			
DLA556	400gm	12	£4.75
DLA556	12.5kg	1	£132.30

LONG TERM HICHEM GREASE

APPLICATIONS:

An exceptional grease, designed for the lubrication of bearings, slides, small gears and valves operating up to temperatures of +280°C and where there is a risk of attack by chemicals, solvents and in the presence of oxygen.

- Perflourinated polyether grease for exceptional lubrication
- Recommended for "lubrication for life" applications
- Excellent up to +280°C
- Anti-wear additives provide savings on component costs

Colour – White

Base – Perflourinated polyether

PRODUCT CODE	PACKAGE SIZE	PACK SIZE	PRICE PER TUB
Long Term Hichem Grease			
DLA553	1kg tubs	1	£350.00

HIGH TEMPERATURE GREASE

APPLICATIONS:

A premium quality grease for use in plain and anti-friction bearings, requiring inherent adhesion and thermal stability, combined with a high temperature rating.

- Excellent high temperature properties
- Resistant to water wash out, corrosion and mild acid attack
- Non-melt thickener
- Temperature range -10°C to +180°C

Colour - Brown, Base - Bentone

PRODUCT CODE	PACKAGE SIZE	PACK SIZE	PRICE PER CARTRIDGE
High Temperature Grease			
DLA550	400gm	12	£6.60
DLA550	12.5kg	1	£186.00

HIGH SPEED GREASE

APPLICATIONS:

With a 'DN' speed rating of 1.2 million, this grease is recommended for the textile industry, high speed spindles on CNC machines and wood-turning equipment.

- Excellent where high speed and high load conditions exist
- Corrosion inhibitors protect components in very humid conditions
- Enables an economic alternative to spray mist systems
- Temperature range -40°C to +130°C

Colour – Brown, Base – Lithium complex

PRODUCT CODE	PACKAGE SIZE	PACK SIZE	PRICE PER CARTRIDGE
High Speed Grease			
DLA555	400gm	12	£11.00
DLA555	12.5kg	1	£255.00

ROTO-SPEC SEMI-FLUID HIGH TEMPERATURE GREASE

APPLICATIONS:

A non-carbonising semi-fluid grease designed for operation at high temperatures particularly where access may be difficult. Suited for economical application to rotary oven bearings in bakeries or other bearings operating at slow speeds or under heavy loads.

- Long lasting at high temperatures
- Resists shock loads and vibration
- Non-fling
- Temperature range: 0° to 450°C (180°C continuous)

Colour – Black, Base – synthetic

PRODUCT CODE	PACKAGE SIZE	PACK SIZE	PRICE PER TUB
Roto-Spec Semi-Fluid High Temp Grease			
DLA5698	400gm	12	£16.20
DLA5698	2.0kg	1	£68.85

EXTREME PRESSURE GREASE

APPLICATIONS:

For the lubrication of bearings under extremely high and shock loading.

- Excellent extreme pressure and anti-wear performance, prolongs component life
- Withstands high shock loads
- Good resistance to water and oil separation
- Wide temperature range -20°C to +140°C

Colour - Brown, Base - Lithium Soap

PRODUCT CODE	PACKAGE SIZE	PACK SIZE	PRICE PER CARTRIDGE
Extreme Pressure Grease			
DLA551	400gm	12	£6.50
DLA551	12.5kg	1	£183.00